



SolarEdge Power Optimizer

Module Add-On

P300 / P350 / P405 / P500



POWER OPTIMIZER

PV power optimization at the module-level

- Up to 25% more energy
- Superior efficiency (99.5%)
- Mitigates all types of modules mismatch-loss, from manufacturing tolerance to partial shading
- Flexible system design for maximum space utilization
- Fast installation with a single bolt
- Next generation maintenance with module level monitoring
- Module-level voltage shutdown for installer and firefighter safety



SolarEdge Power Optimizer Module Add-On

P300 / P350 / P405 / P500

	P300 (for 60-cell modules)	P350 (for high-power 60-cell and for 72-cell modules)	P500 (for 96-cell modules)	P405 (for thin film modules)	
INPUT					
Rated Input DC Power ⁽¹⁾	300	350	500	405	W
Absolute Maximum Input Voltage (Voc at lowest temperature)	48	60	80	125	Vdc
MPPT Operating Range	8 - 48	8 - 60	8 - 80	12.5 - 105	Vdc
Maximum Continuous Input Current (Isc)	Pxxx-2 series Pxxx-5 series	10	11	10	Adc
Maximum Efficiency			99.5		%
Weighted Efficiency			98.8		%
Overvoltage Category			II		
OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING SOLAREEDGE INVERTER)					
Maximum Output Current			15		Adc
Maximum Output Voltage		60		85	Vdc
OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM SOLAREEDGE INVERTER OR SOLAREEDGE INVERTER OFF)					
Safety Output Voltage per Power Optimizer			1		Vdc
STANDARD COMPLIANCE					
EMC		FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3			
Safety		IEC62109-1 (class II safety), UL1741			
RoHS		Yes			
Fire Safety		VDE-AR-E 2100-712:2013-05			
INSTALLATION SPECIFICATIONS					
Maximum Allowed System Voltage			1000		Vdc
Dimensions (W x L x H)	Pxxx-2 series	141 x 212 x 40.5 / 5.55 x 8.34 x 1.59			mm / in
	Pxxx-5 series	128 x 152 x 27.5 / 5 x 5.97 x 1.08	128 x 152 x 35 / 5 x 5.97 x 1.37	128 x 152 x 48 / 5 x 5.97 x 1.89	mm / in
Weight (including cables)	Pxxx-2 series	950 / 2.1			gr / lb
	Pxxx-5 series	770 / 1.7		930 / 2.05	gr / lb
Input Connector			MC4 ⁽²⁾		
Output Connector			MC4		
Output Wire Length	0.95 / 3.0		1.2 / 3.9		m / ft
Operating Temperature Range			-40 - +85 / -40 - +185		°C / °F
Protection Rating	Pxxx-2 series	IP65 / NEMA4			
	Pxxx-5 series	IP68 / NEMA6P			
Relative Humidity			0 - 100		%

⁽¹⁾ Rated STC power of the module. Module of up to +5% power tolerance allowed.

⁽²⁾ For other connector types please contact SolarEdge.

PV SYSTEM DESIGN USING A SOLAREEDGE INVERTER ⁽³⁾		SINGLE PHASE	THREE PHASE
Minimum String Length (Power Optimizers)	P300,P350,P500 P405	8 6	16 13
Maximum String Length (Power Optimizers)		25	50
Maximum Power per String		5250	11250
Parallel Strings of Different Lengths or Orientations		Yes	

⁽³⁾ It is not allowed to mix P405 with P300/P350/P500/P600/P700 in one string.

